



# SAFE STRIP

### DESCRIPTION

A biodegradable alternative to dangerous and caustic stain removers for exterior wood surfaces. Safe Strip has been formulated to be used as a hand stripper or may be applied using your power washer's soap injector. Removes most semi-transparent stains easily. Not for use on solid color or latex stains.

PRODUCT NUMBERS / SHEENS	COATING PROPERTIES	PREPARATION INSTRUCTIONS
<p><b>883</b></p>	<p><b>Weight Solids:</b> 18.3%  <b>Volume Solids:</b> 6.95%  <b>Weight/Gallon:</b> 9.57 lb./gal  <b>Coverage:</b> 500-1000 sq. ft. per gallon at one mil dry film thickness when mixed according to directions.</p>	<p><b>Surface Preparation:</b>  Pre-wet foliage and surrounding work area with water and continue to re-wet as needed</p>
<p><b>PRODUCT ADVANTAGES</b></p> <ul style="list-style-type: none"> <li>➤ Restores Weathered Wood to Natural Color</li> <li>➤ 100% Biodegradable- Will Not Harm Plants or Pets</li> <li>➤ Does Not Contain Chlorine Bleach That May Damage Wood Fibers.</li> <li>➤ Use on All Exterior Wood Surfaces Including Decks, Fences and Fascia</li> <li>➤ New Application Technology Allowing Pressure Washer Injection</li> <li>➤ Removes Most Oil-Based Semi Transparent Stains and Sealers.</li> </ul>	<p><b>VOC (coating):</b> 0.499 lb./gl. or 59.82 g/l  <b>VOC (material):</b> 0.037 lb./gl. or 4.43 g/l  <b>HAPS Ratio:</b> .0526 lbs./gallon</p> <p><b>Shelf Life:</b> 12 months @77° F if unopened and stored in a cool dry area. Always rotate stock.</p> <p><b>Storage:</b> Store in a climate-controlled area, do not allow to freeze.</p> <p><i>Note: These numbers represent actual control values on a smooth, sanded substrate. Spray techniques, texture, and sealing as well as film thickness may give different results on actual work, but they may be used for comparison. To the best of our knowledge, the above technical data is true and accurate at the date of issuance but is subject to change without prior notice.</i></p>	<p><b>Application for Injecting:</b> Put injector hose into undiluted Safe-Strip container. Test a small area to see if desired results are achieved. Inject desired working area (200-300 sq. ft. recommended) Injector ratio 12:1 or lower. Although Safe-Strip has little or no dwell time, 5 minutes of product working time is recommended, (10 minutes for a heavier coating). Do not allow Safe-Strip to dry on surfaces. Pressure wash working area thoroughly. If problem areas persist, repeat above steps.</p> <p><b>Material Preparation for Ready-to-Use:</b>  Pour Safe-Strip into container. Add 4 parts water. One gallon makes 5 gallons, 5 gallons makes 25 gallons. Mix thoroughly. Always test a small inconspicuous area to see if desired results are achieved.</p> <p><b>Application for Ready-To-Use:</b> Apply liberally to wood surfaces. Best application results are with a pump sprayer. After application, always keep working area moist during surface preparation. Once applied you may begin to scrub (no scrubbing necessary with use of pressure washer). When scrubbing the applied area, use synthetic, stiff, bristle brush: do not use a wire or natural bristle brush. Rinse thoroughly with hose or pressure washer. A pressure washer will show the best results.</p> <p><b>Caution:</b> If not used properly, a pressure washer may damage wood. Do not allow Safe-Strip to dry on glass. <b>USE CAUTION WHEN USING SAFE-STRIP, WET SURFACES WILL BE SLIPPERY.</b></p> <p><b>Clean Up:</b> Rinse all equipment with water before storage or reuse. Dispose of in accordance with federal, state, and local regulations regarding pollution.</p>

Revised: June 22, 2017

The following supersedes any provision contained in the forms, letters and papers of your company. This product is designed and intended for professional application only. All products should be thoroughly tested under application conditions prior to use. The information contained herein is believed to be reliable. **HOWEVER, GEMINI MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** UNDER NO CIRCUMSTANCES SHALL GEMINI BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OF WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF GEMINI FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY GEMINI SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER. **CAUTION: DANGER! FLAMMABLE! VAPORS MAY CAUSE FLASH FIRE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. INJURIOUS TO EYES. KEEP OUT OF THE REACH OF CHILDREN!** BEFORE using this product it is essential that the "Material Safety Data Sheet" describing the product as well as the "Product Label" be reviewed. If your company does not have such information or has any questions, contact the manufacturer.